ETERNABOND, INC.

MATERIAL SAFETY DATA SHEET (TACTA010)



941 Oak Street/Elkhart, Indiana 46514 (219) 264-9674 FAX (219) 264-9859 1+800+255-0829



941 Oak Street/Eikhart, Indiana 46514 (219) 264-9674 FAX (219) 264-9859 1+800+253-0829

This form is designed to meet the requirements of the U.S. Labor Department OSHA form no 174.

SECTION I – PRODUCT IDENTIFICATION

Product: ETERNABOND MOLDABLE SEALANT

24 Hour Emergency Assistance - (847) 540-0600

Chemical Name: N/A

Chemical Family: Polyolefin and Synthetic Elastomer

Formula: N/A

HMIS/NFPA HAZARD RATINGS:

Health Hazard:

Flammability Hazard

1

Reactivity Hazard

0

SECTION II – HAZARDOUS COMPONENTS

NONE

SECTION III – PHYSICAL DATA

Boiling Point Range:

420 Degrees Fahrenheit

Percent Volatile by Weight: N/A

Vapor Pressure: N/A

Evaporation Rate: N/A

Vapor Density: N/A

Appearance and Odor: Black and white tapes or gray

Solubility in Water: Insoluble Specific Gravity: 1.04 (adhesive)

sealant

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

Flash Point and Method: Flammable Limits:

450 Degrees Fahrenheit

COC

Extinguishing Media: Carbon dioxide, dry chemical, foam, water fog, and water spray

Special Fire Fighting Procedures: Use water spray to cool fire exposed surfaces and to protect personnel.

Unusual Fire and Explosion Hazards: None

N/A

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: N/A

Effects of Overexposure:

Eves: N/A

Ingestion: Acute oral LD50 is greater than 10g/kg

Inhalation: N/A

Skin: N/A.

Emergency and First Aid Procedures:

Flush with water.

Ingestion: Contact a physician

Inhalation: N/A

Skin: Remove with waterless hand cleaner. Wash with soap and water

Medical Conditions generally aggravated by exposure: N/A

ETERNABOND, INC.

MATERIAL SAFETY DATA SHEET (TACTA010)

Primary Routes of Entry:

Eyes:

None

Ingestion:

Not a normal exposure

Inhalation: None

Skin:

None

Chemicals contained herein listed as carcinogens or potential carcinogens:

NTP: NONE

IARC: NONE

OSHA: NONE

SECTION VI - REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Overheating

Incompatibility (Material to Avoid): Avoid contact with strong oxidizing agents

Hazardous Decomposition Products: None Hazardous Polymerization: Will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Sweep up

Waste disposal method: Dispose of in accordance with Federal, State and local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: N/A

Ventilation: N/A

Eye Protection: Chemical goggles

Protective Gloves: N/A

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing: Do not store near flame, heat or strong oxidizing agents.

SECTION X - NOTES

Note: N/A = not applicable

Issure Date: August 5, 1991 Revision Date: June 20, 1996 NE = not established

Issued By: John Bilstein (KK) Review Date: April 19, 1999

Information herein is given in good faith and is, to the best of our knowledge and belief, accurate and reliable. However, since information herein was obtained, in part, from independent suppliers not under the direction and supervision of ETERNABOND, INC., ETERNABOND, INC., makes no warranty or representation, express or implied, that information is accurate, reliable, complete or representative. ETERNABOND, INC., warrants only that it has made no effort to censor other than trade secret information or to conceal deleterious aspects of its products. The data shown above in no way modifies, amends, or enlarges any specifications or warranty.

All components of this product are listed in the EPA/TSCA Inventory or Chemical Substances.